

# GP 1245

## 12V 4.5Ah

GP 1245 is a general purpose battery with 3-5 years in standby service or more than 260 cycles at 100% discharge in cycle service. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.




### Specification

<b>Cells Per Unit</b>	6
<b>Voltage Per Unit</b>	12
<b>Capacity</b>	4.5Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
<b>Weight</b>	Approx. 1.66kg(3.7 lbs)
<b>Maximum Discharge Current</b>	60/90A(5sec)
<b>Internal Resistance</b>	Approx. 40.5mΩ
<b>Operating Temperature Range</b>	Discharge: -20°C~50°C (-4°F~122°F) Charge: 0°C~40°C (32°F~104°F) Storage: -20°C~40°C (-4°F~104°F)
<b>Nominal Operating Temperature Range</b>	25°C±3°C (77°F±5°F)
<b>Float Charging Voltage</b>	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
<b>Recommended Maximum Charging Current Limit</b>	1.35A
<b>Equalization and Cycle Service</b>	14.4 to 15.0 VDC/unit Average at 25°C (77°F)
<b>Self Discharge</b>	CSB Batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
<b>Terminal</b>	Faston Tab 187/250
<b>Container Material</b>	-ABS (UL94-HB)*Flammability resistance of UL94-V2 can be available upon request.



CSB-manufactured batteries are UL-recognized components under UL924 and UL1989. CSB is also certified by ISO 9001 and ISO 14001.

### Dimensions



### Constant Current Discharge Characteristics Unit:A (25°C,77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	18.67	12.25	9.08	5.37	3.11	1.80	1.26	0.99	0.81	0.54	0.44	0.23
1.67V	17.80	11.78	8.91	5.32	3.10	1.79	1.25	0.98	0.81	0.53	0.44	0.23
1.70V	17.42	11.58	8.83	5.30	3.09	1.79	1.25	0.98	0.81	0.53	0.44	0.23
1.75V	16.21	11.13	8.63	5.22	3.06	1.78	1.25	0.98	0.81	0.53	0.44	0.23
1.80V	15.00	10.67	8.42	5.13	3.03	1.76	1.24	0.98	0.80	0.53	0.43	0.23
1.85V	13.79	10.22	8.22	5.05	3.00	1.75	1.24	0.98	0.80	0.53	0.43	0.23

### Constant Power Discharge Characteristics Unit:W (25°C,77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	224.00	147.00	109.00	64.40	37.30	21.60	15.10	11.90	9.72	6.42	5.27	2.80
1.67V	213.50	141.40	106.90	63.84	37.16	21.53	15.03	11.83	9.69	6.40	5.26	2.79
1.70V	209.00	139.00	106.00	63.60	37.10	21.50	15.00	11.80	9.68	6.39	5.25	2.79
1.75V	194.50	133.50	103.50	62.55	36.75	21.30	14.95	11.75	9.65	6.37	5.21	2.75
1.80V	180.00	128.00	101.00	61.50	36.40	21.10	14.90	11.70	9.61	6.34	5.17	2.70
1.85V	165.50	122.50	98.50	60.45	36.05	20.90	14.85	11.65	9.58	6.32	5.13	2.66

● All mentioned values are average values.


### Trickle (or Float) Service Life




### Capacity Retention Characteristic




### Battery Voltage and Charge Time for Standby Use




### Cycle Service Life



### Battery Voltage and Charge Time for Cycle Use



### Terminal Voltage (V) and Discharge Time (25°C 77°F)



### Charging Procedures

Application	Charge Voltage (V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40~2.50	0.3C
Standby	25°C (77°F)	2.275	2.25~2.30	

### Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C > (A)	0.2C < (A) < 0.5C	0.5C < (A) < 1.0C	(A) > 1.0C

Sales Office URL: [WWW.CSB-BATTERY.COM](http://WWW.CSB-BATTERY.COM)

**CSB BATTERY CO., LTD.**  
**TAIWAN OFFICE**  
 Tel: +886-2-8751-5000  
 Fax: +886-2-8751-6161  
 E-mail: [service@csb-battery.com.tw](mailto:service@csb-battery.com.tw)  
**CSB BATTERY OF NETHERLANDS B.V**  
**NETHERLANDS OFFICE**  
 Tel: +31(0) 180 418 140  
 Fax: +31(0) 180 418 327  
 E-mail: [eurosales@csb-battery.com](mailto:eurosales@csb-battery.com)

**CSB BATTERY (SINGAPORE) PTE., LTD.**  
**SINGAPORE OFFICE**  
 Tel: +65-6742-4944  
 Fax: +65-6742-4744  
 E-mail: [sales@csb-battery.com.sg](mailto:sales@csb-battery.com.sg)  
**CSB BATTERY TECHNOLOGIES, INC.**  
**USA OFFICE**  
 Tel: +1-817-244-7777/1-8003 CSBUSA(272872)  
 Fax: +1-817-244-4445  
 E-mail: [csb@csb-battery.com](mailto:csb@csb-battery.com)

**CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.**  
**SHANGHAI OFFICE**  
 Tel: +86-21-5046-1622, 5046-0833  
 Fax: +86-21-5064-3314

**CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.**  
**BEIJING OFFICE**  
 Tel: +86-10-6597-8060, 6597-8070  
 Fax: +86-10-6597-8050  
 E-mail: [chinasls@csb-battery.com](mailto:chinasls@csb-battery.com)